



PINOUT CONFIGURATION

P1		P2	
1	RED COAX	1	
2	GREEN COAX	2	
3	BLUE COAX	3	
6	RED SHIELD	6	
7	GREEN SHIELD	7	
8	BLUE SHIELD	8	
4		4	
5		5	
9		9	
10		10	
11		11	
12		12	
13		13	
14		14	
15		15	
SHELL	SHIELD	SHELL	

P/N	L±(mm)	BARCODE
V/1M	1000±50	4522686004968
V/2M	2000±50	4522686004975
V/3M	3000±100	4522686004982
V/5M	5000±150	4522686004999

UNIT: mm

ITEM	DESCRIPTION	QTY.	UNIT
1	HD15 MALE CONNECTOR	2	PCS.
2	PAT.NO.: US 6,287,148 B1 RF-BLOK™ SHIELDING METAL CAN	2	PCS.
3	661C BLUE MOLDED PVC HOOD	2	PCS.
4	661C BLUE #4/40 THUMBSCREW	4	PCS.
5	(UL1354 HIGH PRECISION MINI COAX 75Ω WITH SINGLE SHIELDS)x3C+(CONTROL WIRE)x9C+DOUBLE SHIELD OVERALL; BLACK PVC JACKET.	SEE	DWG.

REVISED DETAILS

REVISED BY

Part number:

Revision:

© Copyright 12-2014

JAPAN MATERIAL Co.,Ltd.

V/1M  
V/2M  
V/3M  
V/5M

A

Drawing#: 141217-7

Scale: None

Date: 12/17/2014

TTL13/E/JM/141217-7

PAGE: 1 of 1